

SY210NT4-SSN



Features:

- Multi-Door, 4 Door, 4 Relay, 16*2 LCM New Case
- Stand alone or networking system.
- Built-in Anti-Tamper protection / Buzzer.
- Advanced programmable functions for different level within groups to maximize management control.
- Support multiple proximity, keypad, biometrics, smart card and RS485 / Wiegand reader.
- Versatile software features support wide range functions.
- Capability of connecting external backup power supply for emergency.
- Can be off-line use or on-line use.
- Externally programmable interface.

Specifications :

Number of Cards	:	9,999 cards
Capacity of Records	:	4,200 records
Number of Readers	:	8 (4 IN, 4 OUT)
Door Control	:	4 Door
Control Relay Output	:	Normally 4,expandable to 128
Input Points	:	Normally 4, expandable to 128
Reader Interface	:	RS485
Communication	:	RS485 x 2, Wiegand x 1
Buad Rate	:	19,200bps (4,800bps ~ 115,200bps)
Timer / Time zone	:	32 timer / 60 time zone
Group and APP Set / Holidays	:	64 groups / 366 holidays
Controller ID	:	01~99 (SYW95A) / 0001-9999 (SYSOFT-95A)
Expand Modules	:	SYRIS NT series module
Anti-passback	:	Up to 3 level of local control or group Anti-passback
Keypad	:	16 keys
LED Indicator	:	8 LED
LCD Display	:	16 x 2 character
Support Software	:	SYW95A series / SYSOFT-95A
Input Voltage / Consumption	:	8V ~ 24V DC / 0.3W ~ 3W
Operating / Storage Temperature	:	-20°C ~ +70°C / -40°C ~ +80°C
Dimensions(mm)	:	137W x 180H x 54D
Ordering Information	:	4 door controller, LCM case
Beep Tone	:	Built-in Buzzer / Anti-Tamper Facility